

# Specifications

MODELS	AWP™-20S		AWP™-25S		AWP™-30S	
MEASUREMENTS	US	Metric	US	Metric	US	Metric
Working height*	26 ft 1 in	8.12 m	30 ft 10 in	9.57 m	35 ft 6 in	11.00 m
Platform height	20 ft 1 in	6.12 m	24 ft 10 in	7.57 m	29 ft 6 in	9.00 m
<b>A</b> Height - stowed (Standard, Narrow) stowed (RT)	6 ft 6 in 6 ft 7 in	1.98 m 2.01 m	6 ft 6 in 6 ft 7 in	1.98 m 2.01 m	6 ft 6 in 6 ft 7 in	1.98 m 2.01 m
<b>B</b> tilted back** (Standard)	5 ft 10 in	1.78 m	6 ft .3 in	1.84 m	6 ft 2.5 in	1.89 m
<b>C</b> Length - stowed (Standard) stowed (Narrow) stowed (RT)	4 ft 1 in 4 ft 2 in 5 ft 3 in	1.24 m 1.27 m 1.60 m	4 ft 3.5 in 4 ft 4 in 5 ft 3 in	1.31 m 1.32 m 1.60 m	4 ft 5 in 4 ft 7 in 5 ft 3 in	1.35 m 1.40 m 1.60 m
<b>D</b> Length - tilted back**	6 ft 11 in	2.11 m	6 ft 11 in	2.11 m	6 ft 11 in	2.11 m
<b>E</b> Width (Standard) Width (Narrow) Width (RT)	2 ft 5 in 1 ft 10 in 2 ft 6 in	.74 m .56 m .76 m	2 ft 5 in 1 ft 10 in 2 ft 6 in	.74 m .56 m .76 m	2 ft 5 in 1 ft 10 in 2 ft 6 in	.74 m .56 m .76 m
<b>PRODUCTIVITY</b>						
Lift capacity	350 lbs	159 kg	350 lbs	159 kg	350 lbs	159 kg
ANSI/CSA:						
Outrigger footprint (l/w) (Standard)	5 ft 1 in/4 ft 5 in	1.55/1.35 m	5 ft 1 in/4 ft 5 in	1.55/1.35 m	5 ft 9 in/5 ft 1 in	1.75/1.55 m
<b>F G</b> Outrigger footprint (l/w) (Narrow/RT)	5 ft 4 in/4 ft 2 in	1.63/1.27 m	5 ft 4 in/4 ft 2 in	1.63/1.27 m	6 ft/5 ft	1.83/1.52 m
Corner access*** (Standard)	1 ft 3 in	.38 m	1 ft 2 in	.36 m	1 ft 7 in	.48 m
<b>H</b> Corner access*** (Narrow/RT)	1 ft 2 in	.36 m	1 ft 1 in	.33 m	1 ft 7 in	.48 m
Wall access front/side (Standard)	6 in/1 ft 1 in	.15/.33 m	3 in/1 ft 1 in	.08/.33 m	5 in/1 ft 5 in	.13/.43 m
<b>I J</b> Wall access front/side (Narrow/RT)	9 in/1 ft	.23/.30 m	6 in/1 ft	.15/.30 m	7 in/1 ft 5 in	.18/.43 m
CE/AUS/PB Indoor:						
Outrigger footprint (l/w) (Standard)	5 ft 1 in/4 ft 5 in	1.55/1.35 m	5 ft 9 in/5 ft 1 in	1.75/1.55 m	6 ft 4 in/5 ft 8 in	1.93/1.73 m
<b>F G</b> Outrigger footprint (l/w) (Narrow/RT)	5 ft 11 in/4 ft 10 in	1.80/1.47 m	5 ft 11 in/4 ft 10 in	1.80/1.47 m	6 ft 11 in/6 ft 2 in	2.11/1.88 m
Corner access*** (Standard)	1 ft 3 in	.38 m	1 ft 1 in	.48 m	1 ft 10 in	.56 m
<b>H</b> Corner access*** (Narrow/RT)	1 ft 9 in	.53 m	1 ft 8 in	.51 m	2 ft 3.5 in	.70 m
Wall access front/side (Standard)	6 in/1 ft 1 in	.15/.33 m	7 in/1 ft 5 in	.18/.43 m	8 in/1 ft 9 in	.20/.53 m
<b>I J</b> Wall access front/side (Narrow/RT)	1 ft/1 ft 5 in	.30/.43 m	10 in/1 ft 5 in	.25/.43 m	9 in/1 ft 8 in	.23/.51 m
CE/AUS/PB Outdoor:						
Outrigger footprint (l/w) (Standard)	8 ft 1 in/7 ft 5 in	2.46/2.26 m	9 ft 9 in/9 ft 2 in	2.97/2.79 m	9 ft 9 in/9 ft 2 in	2.97/2.79 m
<b>F G</b> Outrigger footprint (l/w) (Narrow/RT)	9 ft 4 in/9 ft 4 in	2.84/2.84 m	9 ft 4 in/9 ft 4 in	2.84/2.84 m	10 ft 10 in/11 ft 4 in	3.30/3.45 m
Corner access*** (Standard)	1 ft 7 in	.48 m	2 ft 6 in	.76 m	2 ft 3 in	.69 m
<b>H</b> Corner access*** (Narrow/RT)	4 ft 6 in	1.37 m	4 ft 4 in	1.32 m	5 ft 1 in	1.55 m
Wall access front/side (Standard)	1 ft 7 in/2 ft 8 in	.48/.81 m	2 ft 5 in/3 ft 6 in	.74/1.07 m	2 ft 3 in/3 ft 6 in	.69/1.07 m
<b>I J</b> Wall access front/side (Narrow/RT)	2 ft 8 in/3 ft 8 in	.81/1.12m	2 ft 5 in/3 ft 8 in	.74/1.12 m	2 ft 11 in/4 ft 7 in	.89/1.40 m
Platform Dimensions: (l/w/h)						
<b>F G</b> Standard	27/26/44.75 in	.69/.66/1.14 m	27/26/44.75 in	.69/.66/1.14 m	27/26/44.75 in	.69/.66/1.14 m
Gated standard	27/26/44.75 in	.69/.66/1.14 m	27/26/44.75 in	.69/.66/1.14 m	27/26/44.75 in	.69/.66/1.14 m
Gated ultra narrow	22/18/44.75 in	.56/.46/1.14 m	22/18/44.75 in	.56/.46/1.14 m	22/18/44.75 in	.56/.46/1.14 m
<b>H</b> Gated narrow	26/20/44.75 in	.66/.51/1.14 m	26/20/44.75 in	.66/.51/1.14 m	26/20/44.75 in	.66/.51/1.14 m
Standard fiberglass	29/26.5/43.5 in	.74/.67/1.10 m	29/26.5/43.5 in	.74/.67/1.10 m	29/26.5/43.5 in	.74/.67/1.10 m
<b>I J</b> Narrow fiberglass	26/22/43.5 in	.66/.56/1.10 m	26/22/43.5 in	.66/.56/1.10 m	26/22/43.5 in	.66/.56/1.10 m
<b>POWER</b>						
Power source - AC or DC models	12V DC / 110/50-60 Hz or 220/50-60 Hz AC		12V DC / 110/50-60 Hz or 220/50-60 Hz AC		12V DC / 110/50-60 Hz or 220/50-60 Hz AC	
<b>WEIGHT</b>						
AC models (Standard)	677 lbs	307 kg	727 lbs	330 kg	777 lbs	352 kg
AC models (Narrow/RT)	660 lbs	299 kg	694 lbs	315 kg	729 lbs	331 kg
DC models (Standard)	766 lbs	347 kg	817 lbs	371 kg	867 lbs	393 kg
DC models (Narrow/RT)	749 lbs	340 kg	780 lbs	354 kg	818 lbs	371 kg
<b>STANDARDS COMPLIANCE</b>						
	ANSI A92.3, CSA B354.1, CE Compliance, AS 1418.10					